(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 31 March 2005 (31.03.2005)

PCT

(10) International Publication Number WO 2005/028871 A1

(51) International Patent Classification7: F04C 29/00, 29/10, 25/00

(21) International Application Number:

PCT/GB2004/004009

(22) International Filing Date:

20 September 2004 (20.09.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 23 September 2003 (23.09.2003) GB 0322238.7 29 April 2004 (29.04.2004) GB 0409568.3


- (71) Applicant (for all designated States except US): THE BOC GROUP PLC [GB/GB]; Chertsey Road, Windlesham, Surrey GU20 6HJ (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): MANSON, David,

Paul [GB/GB]; BOC Edwards, Unit 2, 23 Dolphin Road, Shoreham by Sea,, West Sussex BN43 6PY (GB). LASKEY, Kristian [GB/GB]; BOC Edwards, Unit 2, 23 Dolphin Road, Shoreham-by-Sea, West Sussex BN43 6PY (GB).

- (74) Agent: BOOTH, Andrew, Steven; The Boc Group Plc, Chertsey Road, Windlesham, Surrey GU20 6HJ (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: CLEANING METHOD OF A ROTARY PISTON VACUUM PUMP



(57) Abstract: A method for managing deposits within a pump mechanism (81) is provided. Fluid suitable for dissolving, diluting or otherwise disengaging deposits which have accumulated on the internal working surfaces of the pump is brought into contact with the mechanism. performance of the pump is monitored and this data is used together with process data received from, or associated with, a tool (83) being evacuated by the pump to calculate (80) fluid flow characteristics which are required to compensate for the accumulation of deposits on the internal working surfaces of the pump. Fluid is then introduced (2, 84) into the pumping mechanism in accordance with the calculated characteristics.

WO 2005/028871 A1



(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

with international search report